



## Dvojcestné guľové ventily RKH

Materiál telesa: Nerezová oceľ  
Rozsah prac. teplôt -20 °C ÷ 60 °C

Vnútrotný závit BSPP

Objednávacie číslo	Prípoje	Svetlosť	Max. tlak	L	i	SW1
			[MPa]	[mm]	[mm]	
RKH G 1/8 DN04	G 1/8"	DN 04	40	69	8	22
RKH G 1/4 DN06	G 1/4"	DN 06	40	69	12	22
RKH G 3/8 DN10	G 3/8"	DN 10	40	69	12	22
RKH G 1/2 DN13	G 1/2"	DN 13	40	85	14	30
RKH G 1/2 DN16	G 1/2"	DN 16	40	84	14	32
RKH G 3/4 DN20	G 3/4"	DN 20	35	96	16	41
RKH G 1 DN25	G 1"	DN 25	35	113	18	46
RKH G 1 1/4 DN32	G 1 1/4"	DN 32	40	110	20	60
RKH G 1 1/2 DN40	G 1 1/2"	DN 40	40	12	22	70
RKH G 2 DN50	G 2"	DN 50	40	140	24	85

## Kuželové pripojenie 24° - pre priame pripojenie na hydraulickú rúru alebo hadicu

Objednávacie číslo	Prípoje	Svetlosť	Max. tlak	L	i	SW1
			[MPa]	[mm]	[mm]	
RKH 06-L DN04	6L (M12x1,5)	DN 04	40	67	7,5	22
RKH 08-L DN06	8L (M14x1,5)	DN 06	40	67	7,5	22
RKH 10-L DN08	10L (M16x1,5)	DN 08	40	71	8,5	22
RKH 12-L DN10	12L (M18x1,5)	DN 10	40	75	8,5	27
RKH 15-L DN13	15L (M22x1,5)	DN 13	40	84	9,5	30
RKH 15-L DN16	15L (M22x1,5)	DN 16	40	83	9,5	32
RKH 18-L DN16	18L (M26x1,5)	DN 16	40	83	9,5	32
RKH 22-L DN20	22L (M30x2)	DN 20	35	102	12	41
RKH 28-L DN25	28L (M36x2)	DN 25	35	108	12	46
RKH 35-L DN32	35L (M45x2)	DN 32	40	128	13,5	60
RKH 42-L DN40	42L (M52x2)	DN 40	40	133	13,5	70
RKH 08-S DN04	8S (M16x1,5)	DN 04	40	73	9,5	22
RKH 10-S DN06	10S (M18x1,5)	DN 06	40	73	9,5	22
RKH 12-S DN08	12S (M20x1,5)	DN 08	40	77	9,5	22
RKH 14-S DN10	14S (M22x1,5)	DN 10	40	84	11,5	27
RKH 16-S DN13	16S (M24x1,5)	DN 13	40	87	11,5	30
RKH 20-S DN16	20S (M30x2)	DN 16	40	91	13,5	32
RKH 25-S DN20	25S (M36x2)	DN 20	35	110	15	41
RKH 30-S DN25	30S (M42x2)	DN 25	35	125	19	55
RKH 38-S DN32	38S (M52x2)	DN 32	40	140	19	60

- guľové ventily RKH je možné dodať aj s prípojmi s NPT závitom alebo s UNF závitom, pre podrobnejšie informácie kontaktujte naše obchodné oddelenie.